



Z0602 Minuette 21<>36 deg Reflector Variable Beam Profile

A versatile unit used for the medium throw front of house positions where hard cut off on the stage edge is required, or soft edge for merging of beams for on stage wash.

The two lens zoom system is adjusted by the heat resistant knobs under the front of the unit between 21 to 36 deg hard edge, the soft edge range is greater.

This beam can be precisely shaped by the use of the four retained (but removable when the cut out is engaged into the side extrusion) shutter blades which have heat resisting handles for easy use. As optional accessories there are a drop in Iris and for Gobo projection (patterns), a rotatable Gobo holder. To give a "Peaked" or "Flat" beam the lamp position is adjustable. The heat resistant rear handle and the 'T' shaped tilt locking knob give easy cool control when adjusting the unit position,

Typical performance based on calibrated T26 650 w Monoplane 400hr 3050K Lamp giving 15,000 Lumen set at Hard edge focus

CCT Minuette Z0602 21-36 Reflector Variable Beam Profile (650W 15,000lm)									
Minimum angle					Maximum angle				
Peak candela (cd)	41,500				Peak candela (cd)	33,000			
Beam Angle (*)	10.0				Beam Angle (*)	16.0			
Cut off angle (*)	21.0				Cut off angle (*)	36.0			
Distance (m)	3	6	9	12	Distance (m)	3	6	9	12
Cut off dia (m)	1.11	2.22	3.33	4.44	Cut off dia (m)	1.95	3.90	5.85	7.80
Peak Illumination (Lux)	4,610	1,150	510	290	Peak Illumination (Lux)	3,665	915	410	230

All photometric data given is indicative of typical performance only. Specifications and materials may be changed without prior notice. Field angle where intensity drops to 10% of peak lux. Beam angle where intensity drops to 50% of peak lux. Cut off angle where intensity drops to zero of peak lux

Reference Information Weight 3.6 kg



Accessories				
Y0122	Scenic Gobo Holder			
Z0100	Rotatable Gobo Holder			
Z0433	Minuette Iris			
Y0016	T18/T25 500w lamp			
Y0018	T26/T27 650w lamp			
Y0012	M38 300w lamp			
Y0014	M40 500w lamp			
Y0057	10mm Spigot			
Z0431	Colour frame			
Y0083	Hook clamp			
Y0082	Safety bond			

CCT Lighting (UK) Limited, Unit 3 Ellesmere Business Park, Haydn Road, Sherwood, Nottingham, NG5 1DX Tel: 44 (0)115 985 8919 Fax: 44 (0)115 985 70971 Email: office@cctlighting.co.uk Website: www.cctlighting.com